



**Application**

**for**

**United States Patent**

**To all whom it may concern:**

*Be it known that we, Robert A. Gentala, John DiDomenico, and Craig S. Rendahl, have invented certain new and useful improvements in*

***OPTICAL PATH STRUCTURE FOR OPEN PATH EMISSIONS SENSING***

*of which the following is a full, clear and exact description:*

099447-0440  
20020124

**OPTICAL PATH STRUCTURE FOR OPEN  
PATH EMISSIONS SENSING**

FIELD OF THE INVENTION

[0001] The present invention relates generally to remote sensing  
5 systems. More particularly, the present invention relates to an apparatus for  
transmitting, reflecting, and detecting light in an open path sensing system such  
as a vehicle emission sensing system, having us in detecting and/or measuring  
one or more components of the air through which the light passes.

BACKGROUND OF THE INVENTION

10 [0002] Current methods of determining whether a vehicle is compliant  
with emission standards include open path and closed path emissions  
measurement systems. In a closed path system, an emission sensor is directly  
connected to the exhaust of the vehicle, such as by insertion into a tailpipe. An  
open path vehicular emissions measurement system collects data by a means  
15 other than a direct connection to the tailpipe, such as a remote sensor that  
analyzes the individual components of emissions. Open path vehicle emission  
systems are often preferable to closed path systems because they can be used in  
numerous locations and do not require the vehicle to stop for testing.

[0003] Various open path emission sensing systems have been  
20 known. One such device uses a radiation source on one side of a roadway that  
projects a beam across the roadway to be received by a detector. The radiation

source and the detector are located on opposite sides of the roadway. The radiation source emits light spectra that may be used to detect an emission signature by way of absorption of light, or which alternatively may be used to excite emission components so as to cause the components to emit light. The  
5 detected emission signature can then be used in various applications, such as the measurement of a vehicle's compliance with emission limits and the determination of the type of fuel that a vehicle is using.

[0004] A disadvantage of many known arrangements is that the radiation sources and detectors must be placed on opposite sides of the roadway  
10 from each other. Since both the detectors and radiation sources require power to operate, this means that a separate power supply must be provided on each side of the roadway.

[0005] Some known arrangements have tried to overcome this problem by using a radiation source on one side of a roadway and a reflective  
15 apparatus located on the other side of the roadway.

[0006] Accordingly, it is desirable to provide an improved optical transmission, reflection, and detection system as herein disclosed.

SUMMARY OF THE INVENTION

[0007] It is therefore a feature and advantage of the present invention  
20 to provide an improved optical transmission, reflection, and detection system. In

20447-224660

accordance with one embodiment of the present invention, a gas component analysis system includes a first light source capable of emitting at least one beam of light having known emission intensities corresponding to a plurality of infrared, visible, and ultraviolet spectra. The system also includes a reflection unit, a detection unit capable of receiving the beam and measuring received intensities corresponding to the plurality of light spectra, and a processor capable of comparing the emission intensities and the received intensities and identifying a concentration of a component corresponding to the intensities.

5  
10  
15  
[0008] Preferably, the system also includes a first off-axis reflector positioned to receive the beam from the first light source and reflect the beam toward the reflection unit. The reflection unit is positioned to receive the beam from the off-axis reflector and reflect the beam. Also preferably, a second off-axis reflector is positioned to direct the beam reflected by the reflection unit so that the beam may be received by the detection unit. Each off-axis reflector preferably comprises a parabolic mirror.

20  
[0009] Also preferably, the system also includes a filter wheel positioned to spin about an axis and receive the beam from the first light source and pass the beam to the reflection unit in pulses. The filter wheel preferably includes a plurality of filters, each of which substantially limits the passage of light to a predetermined spectral wavelength or range of wavelengths.

[0010] Also preferably, the beam of infrared light travels along an optical path to the reflection unit. In this embodiment, the system also includes a second light source capable of emitting a beam of ultraviolet light, as well as a neutral density filter positioned to direct the beam of ultraviolet light along the optical path to the reflection unit. The neutral density filter should be positioned to direct the beam of infrared light to the reflection unit.

[0011] Also preferably, the system also includes a reflector wheel positioned to spin about an axis and receive the beam from the reflection unit and direct infrared components of the beam to the detection unit in pulses.

[0012] In accordance with another embodiment, a method of measuring concentrations of one or more components of a gas includes the steps of: (1) emitting at least one beam of light having known emission intensities corresponding to a plurality of infrared, visible, and ultraviolet spectra through the gas; (2) using a reflection unit to reflect the beam; (3) using a detection unit to receive the beam; (4) measuring received intensities in the beam corresponding to the plurality of light spectra; and (5) identifying a concentration of at least one component of the gas corresponding to a ratio of the emission intensities and the received intensities.

[0013] Preferably, the method embodiment also includes, before the reflecting step, filtering the beam and passing the beam to the reflection unit in

pulses. It may also include, before the detecting step, directing visible and ultraviolet components of the beam and directing infrared components of the beam to the detection unit. Also preferably, in the method embodiment the identifying step is performed by a processing device that is programmed to perform the calculation of a component concentration using a formula corresponding to the Beer-Lambert law.

[0014] There have thus been outlined, rather broadly, the more important features of the invention in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are, of course, additional features of the invention that will be described below and which will form the subject matter of the claims appended hereto.

[0015] In this respect, before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and to the arrangements of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments and of being practiced and carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein, as well as the abstract, are for the purpose of description and should not be regarded as limiting.

[0016] As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for the designing of other structures, methods and systems for carrying out the several purposes of the present invention. It is important, therefore, that the  
5 claims be regarded as including such equivalent constructions insofar as they do not depart from the spirit and scope of the present invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] FIG. 1 illustrates a preferred embodiment of a light source component of the present invention.

10 [0018] FIG. 2 illustrates a preferred embodiment of a reflective element of the present invention.

[0019] FIG. 3 illustrates a preferred embodiment of a detector component of the present invention.

15 [0020] FIG. 4 illustrates an exemplary spectral wheel that may be used in accordance with one embodiment of the present invention.

[0021] FIG. 5 illustrates an alternate embodiment of a detector component of the present invention.

[0022] FIG. 6 illustrates several elements of an exemplary computer of a type suitable for carrying out certain functions of the present invention.

CONFIDENTIAL

DETAILED DESCRIPTION OF PREFERRED  
EMBODIMENTS OF THE INVENTION

[0023] A preferred embodiment of the present invention provides an improved optical transmission, reflection, and detection system for gas component analysis. A preferred embodiment includes a light source unit, which preferably includes an ultraviolet and/or an infrared light source; a reflector unit; and a light detector. Preferably, the light source and detector are included within a single housing. However, the light source and the light detector may optionally be provided in separate housings. The light is transmitted through a gas, such as air containing vehicle emissions, reflected, and detected for analysis and measurement of the amount of absorption that has occurred at known frequencies. The amount of absorption may be used to determine a concentrations of reference gases corresponding to specific frequencies.

[0024] In a preferred embodiment of this invention, infrared, visible, and ultraviolet radiation are combined into one beam, directed across a path such as a road across which vehicles travel and generate exhaust, reflected back across the path, collected and concentrated, separated again, and analyzed by an one or more detectors and/or spectrometers. The infrared light passes through a sequence of filters, preferably narrow bandpass filters, such that each filter is specific to a gas of interest. In one embodiment, a spinning wheel holds the

094292.2900







[0029] The infrared light source item **10** preferably is a low power consumption (preferably less than about ten watts) integrating sphere comprised of a filament positioned around a central member. The filament and member, when energized, emit light, and the sphere, with most or all of its internal surface  
5 comprised of reflective material, concentrates the light to exit through an opening in the sphere, thus creating a pure source of infrared light. Preferably, the light source has little or no cool spots from filament or other material that would interfere with a homogenous transmittance of light. However, other light sources, such as pure bulbs or filaments, may be used.

10 [0030] The visible light source **11** is preferably a light emitting diode (LED) or other visible source, and the ultraviolet light source **12** is preferably an ultraviolet lamp such as deuterium lamp, a xenon lamp, or another lamp that provides ultraviolet light in spectra of interest. The visible light source **11** is focused through an orifice in the ultraviolet lamp, combining the visible and  
15 ultraviolet light (UV/VIS). The filter/mirror **18** preferably is a neutral density filter positioned at an angle to the axis of the beam of UV/VIS light. The neutral density filter **18** acts as a beam combiner, reflecting the light from the infrared source **10** and allowing the UV/VIS light to pass through. The off-axis reflector **26** then collimates the combined light and directs it across the path **22**.

20141024 24242660

[0031] FIG. 2 illustrates an exemplary reflection unit, which in an embodiment used to detect vehicle emissions is preferably placed across the road from the light source component. The reflection unit includes a retro-reflective system, preferably a vertical system and preferably comprising at least three  
5 mirrors positioned to form 90 degree angles with respect to each other. Referring to FIG. 2, incoming light **22** is reflected by a first mirror **30** and a second mirror **32**. The first and second mirror are adjacent or substantially adjacent to each other to form a 90 degree angle. The light reflected by the first and second mirrors is transmitted to a third mirror **34**, which is positioned to be at an  
10 approximately 90 degree angle from the first mirror **30** and second mirror **32**. FIG. 2 illustrates the first mirror **30** along its flat reflective portion, and the second mirror **32** along its edge so that the flat reflective portions of each of the first mirror **30** and second mirror **32** form a 90 degree angle. FIG. 2 illustrates the edge of third mirror **34** such that the flat reflective portion of third mirror **34**  
15 forms a 90 degree angle with the flat reflective portions of both first mirror **30** and second mirror **32**. Light **36** that is reflected by third mirror **34** is then transmitted to the detection unit. Preferably, the angles described above are perfect 90 degree angles, although minor discrepancies may be allowed. The incoming light **22** and/or the reflected light **36** pass through an air component that  
20 is to be measured, such as vehicle emissions.

204240" 224E50



of a Y-shaped split optical fiber cable that sends a portion of the light to each spectrometer. The second is to use a third beam splitter 73 to focus a portion of the light into the visible spectrometer 82 and the other portion into the UV spectrometer 84 (either with or without optical fiber cables) as illustrated in FIG.

- 5 5. In either case, the light can be slightly defocused or overbathe the light orifice of the spectrometer for resistance to vibration and coincident reduction of light with the vibration. Preferably, referring again to FIG. 3, the path 46 along which ultraviolet and/or infrared light is passed comprises one or more cables that pass the light directly to the one or more spectrometers 42 and 43 .

10 [0034] The infrared detector 50 detects the intensity of light along various spectra. The spectra considered correspond to various known components of vehicle exhaust gases. For example, the detector may detect the intensity of light along the following spectra for a measurement of the following vehicle emission components:

<u>Component</u>	<u>Wavelength</u>
Carbon Monoxide (CO)	4.65 $\mu$
Carbon Dioxide (CO <sub>2</sub> )	4.30 $\mu$
HC <sub>1</sub>	3.45 $\mu$
HC <sub>2</sub>	3.17 $\mu$
HC <sub>3</sub>	3.01 $\mu$

HC <sub>4</sub>	3.31 μ
H <sub>2</sub> O	2.75 μ
Reference	3.85 μ

Other wavelengths corresponding to other components, as well as fewer than all of the above-listed wavelengths, may be measured.

5 [0035] Using a processing device, the intensities measured by the detector at each desired wavelength are compared to intensities of light emitted by the source at a reference wavelength using a test to measure the amount of the component associated with the wavelength that was detected in the sample of open air.

10 [0036] Preferably, concentrations of gases may be derived using the Beer-Lambert Law  $L_N(I/I_0) = L$  where LC is the concentration of the component being measured. However, other tests and formulae may be used in alternate embodiments.

15 [0037] The Beer-Lambert Law relates absorbance to concentration where an amount of change  $[dI(\nu)]$  in light intensity  $[I(\nu)]$  at a wavelength  $= \lambda$  is proportional to the concentration of species  $[c(\nu, y)]$  that can absorb frequency  $= \nu$  and may vary in space across the beam in the y direction:

$$dI(\nu) / I(\nu) = kc(\nu, y)dy$$

When this equation is integrated, it becomes:

$$\ln ( I/I_0) = k [(Integral) c(v,y)dy]$$

Where I is the intensity of the sample light; I<sub>0</sub> is the intensity of the reference beam; k is a constant that depends upon the temperature, pressure and molecular structure and; c is the concentration.

5

~~[0038] If the concentration of a pollutant is uniformly distributed along the path length L and the atmosphere has only one absorbing species, then the equation becomes:~~

~~$$\ln (I)/I_0 = -kcL$$~~

~~10 where I is the source light intensity, I<sub>0</sub> is the detected light intensity, and kcL is the concentration of the component being measured. When the atmosphere has more than one absorbing species and the path length is not uniform, then the equation can be written as:~~

~~$$\ln (I)/I_0 = \sum_i -k_i(v_i) \int c_i(v,y)dy$$~~

~~15 where i species are mixed in the plume with varying concentrations c<sub>i</sub> across the plume's width y. The instrument preferably uses a spectral library and this equation to calculate the absorbance and concentration of each species.~~

~~[0039] Using combustion equations enables the simplified equation  $\ln (I)/I_0 = -kcL$  to be applied to the remote sensing device, even though the tailpipe  
20 plume may not be evenly distributed across a traffic lane. The combustion~~

004292.2900  
2/2/2015  
RFB



equations may be used to calculate pollutant concentrations in the undiluted exhaust with the ratios of the pollutants to carbon dioxide.

[0040] In a preferred embodiment, the transmission and detection of light at the wavelengths of mid-infrared listed above is accomplished by using a spinning filter wheel as the filter component (referred to in FIG. 1 as item 16). FIG. 4 illustrates an exemplary spinning filter wheel. Referring to FIG. 4, the spinning filter wheel contains light filters such as 60 and 62 that correspond to wavelengths associated with individual emission components, such as those illustrated in the above chart. The illustration in FIG. 4 illustrates a wheel having eight filters, thus corresponding to the wavelengths and emission components listed in the chart set forth above. However, fewer and/or additional filters, corresponding to fewer and/or additional emission components, may be used in alternate embodiments. Each filter is designed to only allow light of a specific wavelength or wavelength range to pass through it.

[0041] In addition, the filter wheel preferably will have one or more synchronization marks such as 64 that, when detected by a synchronization unit (illustrated in FIG. 1 as item 65), may be used to define either the exact filter or the start of a set of filters that will be in the optical path. The wheel may have one or more opaque areas either between every filter or only between specific filters. The opaque areas prohibit source light from getting to the detector when

2025 RELEASE UNDER E.O. 14176



Referring to FIG. 5, incoming light **70** that is transmitted by the source unit through an emission to be analyzed is reflected by an off-axis reflector **72**, which focuses a light beam **74** onto a first neutral density filter **71** that directs visible light **73** to a visible light spectrometer **82**. Remaining components of the light are

5 focused on a second neutral density filter **77** that focuses reflected light **79** to an ultraviolet spectrometer **84** and reflects light **78** to a rotating mirror **76**. Each neutral density filter directs ultraviolet or visible components of the light stream to a corresponding spectrometer **82** or **84**, preferably via cables or optical fibers, but optionally by direct focus. The rotating mirror **76** preferably is similar to the

10 spinning filter wheel of FIG. 4, except that instead of a rotating mass containing filters, the rotating mass is a single-faceted mirror. The rotating mirror **76** directs infrared light **78** one or more bandpass filters such as **81** that filter the individual spectra and direct the filtered light to corresponding elliptical focusing mirrors **83** that direct light to an infrared detector **80** which may be used to detect individual

15 components of the light. The rotating mirror **76** preferably spins at a speed of up to 60,000 rotations per minute or more, although other speeds may be used.

[0044] FIG. 6 illustrates several elements of a computer processing device that may be used in accordance with a preferred embodiment of the present invention. Referring to FIG. 6, the detector **90** delivers emissions-related data to

20 a processor **92**. The detector may be any of the detectors or spectrometers as

0934204560

illustrated in FIGs. 3 and 5, or any device that receives or contains information collected by such detectors or spectrometers. In the embodiment illustrated in FIG. 6, the detector **90** is part of the unit that contains the processor **92**, and the delivery is performed by a direct link such as a serial bus **94**. However, the processor **92** and detector **90** may be separate, such as with the remote detector **96** illustrated in FIG. 6. Where a remote detector is used, the data may be delivered to the processor **92** by a communications link **100** that delivers the data to an input port **98** such as a communications port. An optional wireless communications link **102** and receiver **105** for such a wireless communication are also illustrated in FIG. 6. The communications link **102** may be a direct wire, a wireless communications link, a global communications network such as the internet, or any other communications medium

[0045] The system illustrated in FIG. 6 also includes a memory **104** which may be a memory such as a hard drive, random access memory and/or read only memory. Other memory devices **106** and **108** such as a CD-ROM, CD-R, DVD, floppy drive, ZIP drive, microdrive, compact flash, or other memory device may also be included. The device also optionally and preferably includes a display **110** and/or a transmitter **112** for providing output to a user or another device.

Attorney for Applicant

[0046] The many features and advantages of the invention are apparent from the detailed specification, and thus, it is intended by the appended claims to cover all such features and advantages of the invention which fall within the true spirits and scope of the invention. Further, since  
5 numerous modifications and variations will readily occur to those skilled in the art, it is not desired to limit the invention to the exact construction and operation illustrated and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the invention.

0046